

Know-How

kubectl Plugins

<https://krew.sigs.k8s.io/plugins/>

Plugin "neat" - Beispiele

```
kubectl get deployment <deploymentname> -n <namespace> -o yaml | kubectl  
neat -f - > deployment.yaml
```

Private Registry/Repository

Abfrage Registry Katalog

```
curl -k https://registry.tuxnet.lan/v2/_catalog
```

Oder mit dem schöneren Tool **reg**

```
reg ls -k registry.tuxnet.lan
```

Docker Images in die private registry kopieren

```
skopeo copy docker://k8s.gcr.io/metrics-server/metrics-server:v0.5.0  
docker://registry.tuxnet.lan/metrics-server/metrics-server:v0.5.0
```

Befüllen der privaten Registry

```
oci-local -u -r registry.tuxnet.lan
```

Löschen von Registry Einträgen/Images mittels crane

```
crane delete "registry.tuxnet.lan/iot/fhem@$(crane digest  
registry.tuxnet.lan/iot/fhem:3.3.0)"
```

Konfiguration der CRE (containerd) für die private Registrie

/etc/containerd/config.toml

```
[plugins."io.containerd.grpc.v1.cri".registry]
  [plugins."io.containerd.grpc.v1.cri".registry.mirrors]
[plugins."io.containerd.grpc.v1.cri".registry.mirrors."registry.tuxnet.lan"]
  endpoint = ["https://registry.tuxnet.lan:32568"]
```

Kubernetes Master-Node welche Ordner/Files auf weitere Master-Nodes kopieren

- Vorbereitungen zum Joinen der weiteren control Nodes
- Sicherung der wesentlichen Dateien, insbesondere der Kubernetes Cluster PKI

```
sudo tar cf kubestrap.tar /etc/kubernetes/admin.conf
/etc/kubernetes/audit.yaml /etc/kubernetes/manifests/lb.yaml
/etc/kubernetes/pki/ca.* /etc/kubernetes/pki/front-proxy-ca.*
/etc/kubernetes/pki/sa* /etc/kubernetes/pki/etcd/ca.*
```

Entpacken dann entsprechend

```
sudo tar xf kubestrap.tar -C /
```

Ausgabe des Token Hash's

```
kubeadm token create --dry-run --print-join-command
```

Zertifikat-Anfragen von Nodes genehmigen

Auflisten aller Anfragen

```
kubectl get csr
```

Anfragen genehmigen

```
kubectl certificate approve <cert-name>
```

Ändern des clusterweiten Konfiguration

Anzeige der aktuellen Cluster Konfig

```
kubectl get cm -n kube-system kubeadm-config -oyaml
```

Ändern der Konfiguration

```
kubectl edit cm -n kube-system kubeadm-config
```

Updating resources

```
kubectl set image deployment/frontend www=image:v2          # Rolling
update "www" containers of "frontend" deployment, updating the image
kubectl rollout history deployment/frontend                  # Check the
history of deployments including the revision
kubectl rollout undo deployment/frontend                     # Rollback
to the previous deployment
kubectl rollout undo deployment/frontend --to-revision=2    # Rollback
to a specific revision
kubectl rollout status -w deployment/frontend               # Watch
rolling update status of "frontend" deployment until completion
kubectl rollout restart deployment/frontend                 # Rolling
restart of the "frontend" deployment
```

new command or entry point for a container

```
apiVersion: v1
kind: Pod
metadata:
  creationTimestamp: null
  labels:
    run: golang
    name: golang
    namespace: testing-chantal
spec:
  containers:
  - name: golang
    image: golang:bookworm
    tty: true
    stdin: true
    command: ["/bin/sh"]
```

```
resources: {}
volumeMounts:
- name: bin
  mountPath: /go/psp-mig
imagePullSecrets:
- name: regcred
dnsPolicy: ClusterFirst
restartPolicy: Always
volumes:
- name: bin
  persistentVolumeClaim:
    claimName: pvc-golang
status: {}
```

Visualize your Kubernetes workloads

k9s

<https://k9scli.io/>

<https://github.com/derailed/k9s/releases>

Octant

<https://octant.dev/>

<https://github.com/vmware-archive/octant/releases>

From:

<https://www.cooltux.net/> - **TuxNet DokuWiki**

Permanent link:

<https://www.cooltux.net/doku.php?id=it-wiki:kubernetes:know-how&rev=1712732346>

Last update: **2024/04/10 06:59**

